

Page 1/11

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

01429-0000

1 Identification

- **Product identifier**
- **Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom**
- **Article number:**
256905, 263453 - 264436, 264757 / 264764, 272073 / 272080, 278310 - 278426, 282638 - 282683, 289941 / 289965, 298738, 314414 - 314469, 325489, 325496, 321337 - 321818, 351945 - 352317, 352232, 352249, 352256, 352263, 352300, 352317, 381126, 386312 - 386510, 745294
- **Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the mixture Lacquer**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
L&G Vertriebs GmbH
Häusserstr. 36
D-69115 Heidelberg
Tel. +49-6221-36333-30
Fax +49-6221-36333-33
info@montana-cans.de
www.montana-cans.com
- **Information department: Department Product Safety**
- **Emergency telephone number:**
Tel.: +49 6266-75-310
Fax +49 6266-75-362
(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

2 Hazard(s) identification

- **Information concerning particular hazards for human and environment:**
The product has to be labeled due to the calculation procedure of international guidelines.
Warning! Pressurized container.
- **Label elements**
- **Hazard-determining components of labeling:**
xylene, mixture of isomers
- **Risk phrases:**
Extremely flammable.
Harmful by inhalation and in contact with skin.
- **Safety phrases:**
Keep out of the reach of children.
Keep away from sources of ignition - No smoking.
Do not breathe vapour.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Wear suitable protective clothing and gloves.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.
- **Special labeling of certain preparations:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material.
Buildup of explosive mixtures possible without sufficient ventilation.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**
Health = 2
Fire = 4
Reactivity = 3

(Contd. on page 2)

USA

Page 2/11

Safety Data Sheet acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 1)

- **HMIS-ratings (scale 0 - 4)**
- Health = 2
- Fire = 4
- Reactivity = 3
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT: Not applicable.**
- **vPvB: Not applicable.**

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Mixture of the substances listed below with nonhazardous additions.**

· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 RTECS: ZE 2100000 Reg.nr.: 02-2119752448-30	xylene, mixture of isomers Xn R20/21; Xi R38 R10	12.5-<20%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49	acetone Xi R36; F R11 R66-67	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 RTECS: TX 2275000 Reg.nr.: 01-2119486944-21	propane F+ R12	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 RTECS: EJ 4200000 Reg.nr.: 01-2119474691-32	butane F+ R12	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 RTECS: TZ 4300000	isobutane F+ R12	2.5-<5.0%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10	2.5-<5.0%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 RTECS: DA 0700000 Reg.nr.: 02-2119752523-40	ethylbenzene Xn R20; F R11	<2.5%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Xn R65; Xi R37; N R51/53 R10-66-67	<2.5%

· **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

(Contd. on page 3)

USA

Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 2)

For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

USA

Page 4/11

Safety Data Sheet acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility: Not required.**
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class: 2B**
- **Specific end use(s) No further relevant information available.**

8 Exposure controls/personal protection

- **Additional information about design of technical systems: No further data; see item 7.**
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene, mixture of isomers

PEL () Long-term value: 435 mg/m³, 100 ppm

REL () Short-term value: 655 mg/m³, 150 ppm

TLV () Long-term value: 435 mg/m³, 100 ppm

Short-term value: 651 mg/m³, 150 ppm

Long-term value: 434 mg/m³, 100 ppm

BEI

67-64-1 acetone

PEL () Long-term value: 2400 mg/m³, 1000 ppm

REL () Long-term value: 590 mg/m³, 250 ppm

TLV () Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm

Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm

BEI

74-98-6 propane

PEL () Long-term value: 1800 mg/m³, 1000 ppm

REL () Long-term value: 1800 mg/m³, 1000 ppm

TLV () refer to Appendix F: minimal oxygen content

106-97-8 butane

REL () Long-term value: 1900 mg/m³, 800 ppm

TLV () Short-term value: 2370 mg/m³, 1000 ppm

75-28-5 isobutane

TLV () Short-term value: 2370 mg/m³, 1000 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEEL () Long-term value: 50 ppm

100-41-4 ethylbenzene

PEL () Long-term value: 435 mg/m³, 100 ppm

REL () Short-term value: 545 mg/m³, 125 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV () Short-term value: 543 mg/m³, 125 ppm

Long-term value: 87 mg/m³, 20 ppm

BEI

(Contd. on page 5)

USA

Page 5/11

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 4)

Ingredients with biological limit values:	
1330-20-7 xylene, mixture of isomers	
BEI ()	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
67-64-1 acetone	
BEI ()	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
100-41-4 ethylbenzene	
BEI ()	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

Breathing equipment:

Filter AX
Not necessary if room is well-ventilated.

Protection of hands:

Protective gloves
Solvent resistant gloves
In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves Butyl rubber, BR

Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:
Acetone: 480 min
Butyl acetate: 60 min
Ethyl acetate: 170 min
Xylene: 42 min

Eye protection: Safety glasses

USA

(Contd. on page 6)

Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 5)

9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.

- Flash point: Not applicable, as aerosol.

- Flammability (solid, gaseous): Not applicable.

- Decomposition temperature: Not determined.

- Auto igniting: Product is not selfigniting.

- Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

- Explosion limits:

Lower:	1.1 Vol %
Upper:	13.0 Vol %

- Vapor pressure at 20 °C (68 °F): 8300 hPa (6226 mm Hg)

- Density at 20 °C (68 °F): 0.98 g/cm³ (8.178 lbs/gal)

- Relative density: Not determined.

- Vapour density: Not determined.

- Evaporation rate: Not applicable.

- Solubility in / Miscibility with

- Water: Not miscible or difficult to mix.

- Partition coefficient (n-octanol/water): Not determined.

- Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

- Solvent content:

VOC-USA	50.7 %
	638.8 g/l / 5.33 lb/gl

- Other information: No further relevant information available.

10 Stability and reactivity

- Reactivity

- Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- Possibility of hazardous reactions: No dangerous reactions known.

- Conditions to avoid: No further relevant information available.

- Incompatible materials: No further relevant information available.

- Hazardous decomposition products: No dangerous decomposition products known.

USA

(Contd. on page 7)

Page 7/11

Safety Data Sheet acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 6)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

LD/LC50 values that are relevant for classification:

1330-20-7 xylene, mixture of isomers

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6350 mg/l (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	3592 mg/kg (rat) (ECD-Prüfrichtlinie 401)
Dermal	LD50	>3160 mg/kg (rab) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- Primary irritant effect:
 - on the skin: No irritant effect.
 - on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Harmful
 - Vapors have narcotic effect.
- Carcinogenic categories

IARC (International Agency for Research on Cancer)

1330-20-7	xylene, mixture of isomers	3
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
7631-86-9	silicon dioxide, chemically prepared	3
14808-60-7	Quartz (SiO ₂)	1
NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K

12 Ecological information

- Toxicity

Aquatic toxicity:

1330-20-7 xylene, mixture of isomers

EC50 (24h)	>175 mg/l (bacteria)
EC50 / 48h	3.82 mg/l (daphnia magna / Wasserfloh)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)

64742-95-6 Solvent naphtha (petroleum), light arom.

EC50 / 48h	>100 mg/l (daphnia magna / Wasserfloh)
EC50/96h	19 mg/l (desmdesmus subspicatus / Grünalge) (OECD - Prüfrichtlinie 201)
LC50/96h	>100 mg/l (Regenbogenforelle) (67/548/EWG Annex 5 C.1.)

(Contd. on page 8)

USA

Page 8/11

Safety Data Sheet acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 7)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
- **Water hazard class 2 (Self-assessment): hazardous for water**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------------|
| · UN-Number | UN1950 |
| · DOT, ADR, IMDG, IATA | UN1950 |
| · UN proper shipping name | Aerosols, flammable |
| · DOT | UN1950 Aerosols |
| · ADR | AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |
| · Transport hazard class(es) | |
| · DOT, IMDG, IATA | 2.1 |
| · Class | 2.1 |
| · Label | 2.1 |
| · ADR | |
| · Class | 2 5F Gases |
| · Label | 2.1 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Void |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Gases |
| · Danger code (Kemler): | - |
| · EMS Number: | F-D,S-U |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | UN1950, Aerosols, 2.1 |

USA

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: **Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom**

(Contd. of page 8)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture .

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene, mixture of isomers

100-41-4 ethylbenzene

· TSCA (Toxic Substances Control Act):

67-64-1 acetone

106-97-8 butane

74-98-6 propane

13463-67-7 titanium dioxide

108-65-6 2-methoxy-1-methylethyl acetate

100-41-4 ethylbenzene

1345-05-7 Zinksulfid-Barium-Mischsalz

64742-95-6 Solvent naphtha (petroleum), light arom.

7631-86-9 silicon dioxide, chemically prepared

96-29-7 2-butanone oxime

64742-48-9 Naphtha (petroleum), hydrotreated heavy

14808-60-7 Quartz (SiO₂)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene, mixture of isomers

I

67-64-1 acetone

I

100-41-4 ethylbenzene

D

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene, mixture of isomers

A4

67-64-1 acetone

A4

13463-67-7 titanium dioxide

A4

100-41-4 ethylbenzene

A3

14808-60-7 Quartz (SiO₂)

A2

· MAK (German Maximum Workplace Concentration)

13463-67-7 titanium dioxide

3A

100-41-4 ethylbenzene

3A

96-29-7 2-butanone oxime

2

(Contd. on page 10)

USA

Page 10/11

Safety Data Sheet acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 9)	
14808-60-7	Quartz (SiO ₂)
1	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO ₂)
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
· Hazard symbols:	
Xn Harmful	
F+ Extremely flammable	
· Hazard-determining components of labeling:	
xylene, mixture of isomers	
· Risk phrases:	
Extremely flammable.	
Harmful by inhalation and in contact with skin.	
· Safety phrases:	
Keep out of the reach of children.	
Keep away from sources of ignition - No smoking.	
Do not breathe vapour.	
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.	
Wear suitable protective clothing and gloves.	
If swallowed, seek medical advice immediately and show this container or label.	
Use only in well-ventilated areas.	
· Special labeling of certain preparations:	
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.	
Do not spray on a naked flame or any incandescent material.	
Buildup of explosive mixtures possible without sufficient ventilation.	
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R36 Irritating to eyes.

R37 Irritating to respiratory system.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Contact: Anwendungstechnik**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)

USA

Page 11/11

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/09/2013

Reviewed on 12/09/2013

Trade name: Montana Black Lackspray 150 / 400ml alle Farbtöne + silber-, gold- und kupferchrom

(Contd. of page 10)

DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

USA

Item Numbers: 01429-1010, 01429-1020, 01429-1030, 01429-1040, 01429-1050, 01429-1060, 01429-1070, 01429-1080, 01429-1090, 01429-1100, 01429-1110, 01429-1120, 01429-1130, 01429-1140, 01429-1150, 01429-1160, 01429-1170, 01429-1180, 01429-1190, 01429-1200, 01429-1210, 01429-1220, 01429-1230, 01429-1240, 01429-1250, 01429-1260, 01429-1270, 01429-1280, 01429-1290, 01429-1300, 01429-1310, 01429-1320, 01429-1330, 01429-1340, 01429-1350, 01429-1360, 01429-1370, 01429-1380, 01429-1390, 01429-1400, 01429-1410, 01429-1420, 01429-1430, 01429-1440, 01429-1450, 01429-1460, 01429-1470, 01429-1480, 01429-1490, 01429-1500, 01429-1510, 01429-1520, 01429-1530, 01429-1540, 01429-1550, 01429-1560, 01429-1570, 01429-1580, 01429-1610, 01429-1620, 01429-1630, 01429-1640, 01429-1650, 01429-1660, 01429-1670, 01429-1680, 01429-1690, 01429-1700, 01429-1710, 01429-1720, 01429-1730, 01429-1740, 01429-1750, 01429-1760, 01429-1770, 01429-1780, 01429-1790, 01429-1800, 01429-1810, 01429-1820, 01429-1830, 01429-1840, 01429-2020, 01429-2180, 01429-2220, 01429-2580, 01429-2590, 01429-2610, 01429-3010, 01429-3040, 01429-3050, 01429-3060, 01429-3090, 01429-3110, 01429-3120, 01429-3130, 01429-3140, 01429-3150, 01429-3160, 01429-3190, 01429-3230, 01429-3340, 01429-3450, 01429-3550, 01429-3790, 01429-3900, 01429-4010, 01429-4020, 01429-4030, 01429-4040, 01429-4050, 01429-4090, 01429-4300, 01429-4510, 01429-4580, 01429-4590, 01429-4600, 01429-4910, 01429-4920, 01429-4930, 01429-4940, 01429-5010, 01429-5020, 01429-5050, 01429-5140, 01429-5230, 01429-5290, 01429-5350, 01429-5450, 01429-5550, 01429-5560, 01429-5590, 01429-5900, 01429-5910, 01429-5920, 01429-5930, 01429-5990, 01429-6040, 01429-6110, 01429-6410, 01429-6510, 01429-6590, 01429-6890, 01429-7010, 01429-7040, 01429-7050, 01429-7060, 01429-7070, 01429-7080, 01429-7090, 01429-7100, 01429-7110, 01429-7240, 01429-7330, 01429-7370, 01429-7730, 01429-7890, 01429-7910, 01429-7930, 01429-8100, 01429-8140, 01429-8220, 01429-8430, 01429-8480, 01429-8540, 01429-8930, 01429-9010, 01429-9320, 01429-9330, 01429-9500, 01429-2300, 01429-2310, 01429-2320, 01429-2330, 01429-2340, 01429-2350, 01429-2360, 01429-2370, 01429-2380, 01429-2390, 01429-2400, 01429-2410, 01429-2420, 01429-2430, 01429-2440, 01429-2450, 01429-2460